

Basic unit	
Power supply	100 – 240 V / 50/60 Hz; 220 V / 60Hz
Fuse	2 x T3A15L, 250V
Power consumption	250VA
Protection class	I
Application class	BF
Frequency	1 Hz – 22 Hz, adjustable in 1 Hz-steps 3 burst modes with 4, 8 or 12 pulses
Shock energy levels	60 – 185 mJ (at applicator) freely selectable in 10mJ steps at 22 Hz max. 90 mJ at 16 Hz max. 120 mJ at 10 Hz max. 185mJ
Operating mode	Interval max. 6000 beats / 15 min. pause
Accuracy	± 20%
Dimensions	322 mm x 235 mm x 130 mm
Weight	2.7 kg
Handpiece	
Dimensions	230 mm long, diameter 50 mm
Weight	850 g
Useful life	2,000,000 shocks (minimum)
Applicator heads	6 / 15 / 25 mm diameter / changeable without tools
Complete device	
Dimensions	580 mm x 250 mm x 470 mm (complete with case)
Total weight	13 kg (complete with case)
Operation	10 to 25°C, 20% to 80% rel. humidity, without condensation at 700 hPa–1060 hPa
Transport	-10 °C to +50°C, 10% to 90% rel. humidity, without condensation at 700 hPa–1060 hPa
Storage	-10 °C to +50°C, 10% to 90% rel. humidity, without condensation at 700 hPa–1060 hPa

Note: Store and transport only in original packing.

